

FINN

FINN Machines

HydroSeeder



HydroSeeder



PRODUCT INFORMATION



Product Name:

FINN HydroSeeder Models – are available for every size job.

Variable Speed Agitation:

FINN features 100% hydraulically driven, mechanical paddle agitation, that is independent of the engine rpm. This allows for fingertip control of both agitator speed and paddle direction, enhancing the loading, mixing, and discharge processes.

Liquid Recirculation:

The standard recirculation line provides for pressure relief when utilizing the remote shutoff valve at the end of the hose. Recirculation is also helpful in keeping heavy solids such as granular lime and fertilizers in suspension.

Direct Pump Drive:

FINN's unique direct drive configuration utilizes an in-line, single shaft clutch/pump design. This provides better torque utilisation, achieving greater discharge distance while reducing maintenance.

Exclusive Pump:

Specially designed by FINN to handle thick, hydraulic mulch slurries, the standard centrifugal pump can easily be adjusted in the field. .

Hose Reel Option:

Electric or hydraulic hose reels can be added to any HydroSeeder model, making detail work and hose storage easy.

Ergonomic Boom:

The exclusive discharge boom design is dynamically balanced for operator comfort while handling high discharge pressures.

Consumables:

The FINN Hydroseeding Consumables are an exclusive blend of premium products that create the ideal growing environment.



FINN HYDROSEEDER	LIQUID CAPACITY	POWER	ENGINE	EMPTY WEIGHT	WORKING WEIGHT	DIMENSIONS
T30	1268 L	11 KW	KOHLER BENZIN	671 KG	2068 KG	2,47 m L x 1,55 m H x 1,16 m B
T60S	2271 L	18 KW	KOHLER BENZIN	984 KG	3252 KG	3,40 m L x 1,37 m H x 1,75 m B
T60T	2271 L	18 KW	KOHLER BENZIN	1256 KG	3524 KG	4,30 m L x 2,74 m H x 1,75 m B
T75S	3104 L	18 KW	KOHLER BENZIN	1111 KG	4168 KG	4,16 m L x 1,37 m H x 1,75 m B
T75T	3104 L	18 KW	KOHLER BENZIN	1474 KG	4531 KG	5,06 m L x 2,74 m H x 1,75 m B
T90S	3558 L	25 KW	KUBOTA DIESEL	1814 KG	6010 KG	3,35 m L x 2,57 m H x 2,03 m B
T90T	3558 L	25 KW	KUBOTA DIESEL	2458 KG	6654 KG	4,94 m L x 2,74 m H x 2,16 m B
T120S	4466 L	25 KW	KUBOTA DIESEL	2032 KG	7294 KG	3,91 m L x 2,57 m H x 2,03 m B
T120T	4466 L	25 KW	KUBOTA DIESEL	2630 KG	7893 KG	5,67 m L x 2,94 m H x 2,23 m B
T120GN	4466 L	25 KW	KUBOTA DIESEL	2730 KG	7992 KG	6,33 m L x 2,99 m H x 2,13 m B
T170	6624 L	53 KW	KUBOTA DIESEL	2948 KG	10841 KG	4,86 m L x 2,52 m H x 2,48 m B
T280	10410 L	85 KW	JOHN DEERE DIESEL	4059 KG	16148 KG	5,57 m L x 2,72 m H x 2,28 m B
T330	12492 L	85 KW	JOHN DEERE DIESEL	4354 KG	19051 KG	6,28 m L x 2,72 m H x 2,28 m B



Internationale Geotextil GmbH

Am Bahnhof 54-27239 Twistringener – Germany - Tel +49 (0) 42 43 92 88-73 –Fax +49(0) 42 43 92 88-22
Info@igg.de www.igg.de